

**DİKEY SAC PLAKA KALDIRMA APARATI / UNIVERSAL PLATE CLAMP**

		SL-HPZ 05	SL-HPZ 10	SL-HPZ 20	SL-HPZ 30	SL-HPZ 50	
<b>Kaldırma kapasitesi / Capacity</b>		<b>0.5</b>	<b>1.0</b>	<b>2.0</b>	<b>3.0</b>	<b>5.0</b>	t
<b>Test yükü / Proof test load</b>		<b>7.35</b>	<b>14.7</b>	<b>29.4</b>	<b>44.1</b>	<b>73.5</b>	kN
<b>Ağız açıklığı / Jaw opening</b>		<b>0-15</b>	<b>0-20</b>	<b>0-25</b>	<b>0-30</b>	<b>0-50</b>	mm
<b>Ölçüler / Dimensions</b>	A	30	48	70	75	80	mm
	B	44	63	76	85	90	mm
	C	35	51	56	59	65	mm
	D	0-17	0-22	0-27	0-32	0-52	mm
	E	103	138	164	193	240	mm
	F	10	12	16	20	22	mm
	G	212	295	370	418	450	mm
	H	35	51	52	78	88	mm
<b>Ağırlık / Weight</b>		<b>1.9</b>	<b>4.8</b>	<b>6.5</b>	<b>14.8</b>	<b>22.5</b>	kg

- Sacı, farklı açılardan güvenle kaldırmanızı sağlayan özel dizayn.
- Her pozisyonda sacın sağlam tutulmasını sağlayan oynar mapa.
- Güvenli tutuş ve kilitleme mekanizması için sert çelikten yapılmış çeneler.
- HRC30/Brinell300 ve üstü çelik tiplerine uygun
- % 150 aşırı yük testli.
- EC Council Directive2006/ 42 EC Machinery, ve American Standard ANSI/ASME B30.20'ye uygun üretilmiştir.

- Designed for the safe handling of plate at various angles.
- The pivoting shackle ensures adequate gripping pressure to hold the plate safely in every position.
- Hardened steel jaws for positive grip and locking mechanism.
- Suitable for all structural steel up to HRC30/Brinell 300.
- 150 % overload factory tested.
- Manufactured according to EC Council Directive 2006/42 EC Machinery, American Standard ANSI/ASME B30.20.

